



# AIR FLO 2

## DIFFUSED AERATION


- » No electrical parts in water, safe for recreational use.
- » Extremely energy efficient and cost effective.
- » Choose between self cleaning dome diffusers or stone diffusers.
- » Operating depths up to 40ft+ or 12.2m+.
- » 2 year all-inclusive warranty.
- » Complete package includes compressor(s), cabinet, cabinet base, diffuser(s), valve box, valves, filter, clamps and skid.
- » Safety tested and listed with ETL & ETL-C, conforming to UL standards; and carries a 3rd party listing with CE.

60HZ	Compressors	Manifold(s)	Area Affected (Acres)	Operating Depth (ft)	Volume (GPM) Influenced	Volt/Ph/Amp 1725 @ 28 PSI*
System 1	1	2	to 1/2 to 1 to 3 to 3	4-7 8-14 14-19 19-40	2250 3250 3750 4000+	115/1/8 230/1/3
System 2	1	1	to 1/2 to 1 to 3	8-26 14-26 19-40	4000+	115/1/8 230/1/3
System 3	2	4	to 1 to 5	4-7 8-18	2250 3750	115/1/14.5 230/1/6
System 4	2	6	to 3 to 8 to 12	4-7 8-18 14-19	2250 3250 3750	115/1/14.5 230/1/6
System 5	1	3	to 3	8-14	3250	115/1/8 230/1/3
System 6	2	2	to 5	19-40	4000+	115/1/14.5 230/1/6

\* Running amp draw is per 3/4HP compressor.



Stone Diffuser Manifold



Dome Diffuser Manifold

### PRODUCT ILLUSTRATIONS

- Air Flo 2 Diffused Air Systems incorporate 3/4HP piston compressors allowing for operating depths up to 40ft or 12m.
- Choose from either self cleaning dome diffuser manifolds, or stone diffuser manifolds.
- Enhanced cabinet construction is corrosion resistant, provides quieter operation and simplified servicing.
- Clean air intake system improves performance through the new air filter system and includes an auto thermal protection circuit.
- Combined with the provided shore mounted valve box, the Air Flo 2 allows for shorter tubing requirements offering significant cost savings.

Minimum operating depth varies, visit [www.otterbine.com](http://www.otterbine.com) for product testing and package details, along with dB ratings for the Air Flo 2 and efficiency at depth charts.

Product specifications and CADs can be found online through [www.otterbine.com](http://www.otterbine.com) or [www.caddetails.com](http://www.caddetails.com)